# **Product datasheet**

#### **AMBIENT**



# AM2120DS2500840DB



# AMBIENT G2 IND 1200 D/I D NW OP/OP DA B

# Description:

LAMP surface wall mounted fixture AMBIENT G2 IND 1200 D/I Double Switch. Manufactured from extruded aluminum with an 75% recycling rate with Opal polycarbonate diffusers. Model for LED MID-POWER, colour temperature 4000K and IRC80. Electronic DALI gear included. IP40, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: >72.000 L80B10. Available luminaire body finishes: White and black. Frontal accessory sold separately with the desired finish. White, Black, Raw o Anodised (Gold, Bronze, Champagne, Blue and Black).



Finish: Matte black RAL 9011 1.200 x 80 x 48 mm Dimensions:

Installation: Wall mounted

# **TECHNICAL SPECIFICATIONS:**

Light output: 4.154 lm °K: 4000 Plum: 34,5W CRI: 80 Efficacy: 120,4 lm/w 3 MacAdam:

Type: MID POWER Power Supply: 220-240V 50/60Hz LED Lifetime: >72.000 L80B10 (Ta=25°C) Gear: Adjustable DALI

Power: 32W

#### Light output tolerance +/- 10%



CLASE

























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU














# **AMBIENT**







# **PHOTOMETRIC DATA:**

AM2120DS25OO840DB  $\eta$  = 100% Imax = 188 cd/kIm UTE: 0,50E + 0,50T Image CIE: 49 81 97 50 100








# **AMBIENT**



**ACCESORIES: Assembly** 



Product code: AM2ACIN120ABK



AMBIENT G2 ACC FRONT IND 1200 AN. BLACK



AM2ACIN120ABL

Description: AMBIENT G2 ACC FRONT IND 1200 AN. BLUE



Product code: AM2ACIN120ABZ

Description: Product code:

AMBIENT G2 ACC FRONT IND 1200 AN. BRONZE



AM2ACIN120ACH

Description: AMBIENT G2 ACC FRONT IND 1200 AN. CHAMP



Product code: AM2ACIN120AGD



AMBIENT G2 ACC FRONT IND 1200 AN. GOLD



AM2ACIN120ARW

Description:

AMBIENT G2 ACC FRONT IND 1200 AL RAW



Product code: AM2ACIN120B

Description:

AMBIENT G2 ACC FRONT IND 1200MM BK



Product code:

AM2ACIN120W

Description:

AMBIENT G2 ACC FRONT IND 1200MM WH

Data according to regulations 2019/2020/EU and 2019/2015/EU