#### **B-SIDE LED**


#### BS2188515840NA



#### B-SIDE G2 180º 850 1500 NW ANT

#### Description:

Bollard model B-SIDE G2 180° LED 850 1500, LAMP brand. Manufactured from die-cast aluminium and extruded body of recycled aluminium with an 80% lacquered rate and translucent diffuser. 850mm height. Its base has an anti-corrosion electro coating treatment. 4000K CRI 80 LED. Control gear included. IP65, IK06 protection rating. Insulation class I. Lifetime: 64. 000 L80 B10. BUG Rate: B0 U2 G1, ULOR: 7,4%. Available finishes: anthracite and textured grey.



Finish: Textured anthracite

Dimensions: Ø 160 mm x 850 mm Weight: 4.384 g

Installation: Standing

#### **TECHNICAL SPECIFICATIONS:**

Light output: 429 lm °K: 4000 Plum: 9,9W CRI: 80 Efficacy: 43,3 lm/w 3 MacAdam:

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 64.000 L80 B10 (Ta=25°C) Gear: Electronic

8,9W Power:

### Light output tolerance +/- 10%













**IP** 

65







# **CUSTOM MADE OPTIONS:**


























Data according to regulations 2019/2020/EU and 2019/2015/EU

## **B-SIDE LED**










### **PHOTOMETRIC DATA:**

BS2188515840NA  $\eta$  = 100% lmax = 502 cd/klm UTE: 0,08T lmax = 100 CIE: 12 47 82 92 100







Data according to regulations 2019/2020/EU and 2019/2015/EU