Product datasheet

B-SIDE LED

BS2362510840NG



B-SIDE G2 360° 250 1200 NW GR

Description:

Bollard model B-SIDE G2 360° LED 250 1200, LAMP brand. Made of lacquered aluminium injection, and translucent polycarbonate diffuser. 250mm height. Its base has an anti-corrosion electro coating treatment. 4000K CRI 80 LED. Control gear included. IP65, IK06 protection rating. Insulation class I. Lifetime: 72. 000 L80 B10. BUG Rate: B0 U2 G1, ULOR: 3,5%. Available finishes: anthracite and textured grey.



Finish:Texturised greyDimensions:Ø 160 mm x 450 mmWeight: 3.620 g

Installation: Standing

TECHNICAL SPECIFICATIONS:

Light output:	560 lm	⁰К:	4000
Plum:	8,7W	CRI :	80
Efficacy:	61,4 lm/w	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	6,5W		

Light output tolerance +/- 10%



CUSTOM MADE OPTIONS:




LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

B-SIDE LED

BS2362510840NG

B-SIDE G2 360° 250 1200 NW GR





Worktitude for light