FIL35



F31RE084MOOC830DG

- FIL35 REC 840 2220 WW OP COMF DALI GR.

Description:				
Finish: Gloss	grey			
Installation: Re	ecessed			
TECHNICAL SPI	ECIFICATIONS:			
Light output:	1.179 lm	°K :	3000	
Plum:	13,5W	CRI:	80	
Efficacy:	87,3 lm/w	MacAdam:	3	
UGR:	<19	Power Supply:	220-240V 50/60Hz	
Туре:	MID POWER LED	Gear:	Adjustable DALI	
LED Lifetime:	70.000 L80 B10 (Ta=25°C)			
Power:	12W			
Light output toler	ance +/- 10%			



FIL35








FIL35 REC 840 2220 WW OP COMF DALI GR.

PHOTOMETRIC DATA:

F31RE084MOOC830DG η = 99% lmax = 693 cd/klm UTE: 0,99C CIE: 70 93 100 100 99







Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.