FIL35



F31RE084MOOP840DB

- FIL35 REC 840 2220 NW OPAL DALI BK.

Description:



Finish: Matte black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 1.329 lm
 ⁰K :
 4000

 Plum:
 13,5W
 CRI :
 80

 Efficacy:
 98,4 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 70.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 12W

Light output tolerance +/- 10%

EPD

FIL35







FIL35 REC 840 2220 NW OPAL DALI BK.


PHOTOMETRIC DATA:


F31RE084MOOP840DB η = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.