FIL35



E24	DE	1421	100	C830	MID
ro i	RE	1 Z IV	IUU	Lost	JING

FIL35 REC 1120 2960 WW OP COMF BK. Description: Finish: Matte black RAL 9011 Installation: Recessed **TECHNICAL SPECIFICATIONS:** Light output: 1.571 lm °K: 3000 Plum: 18W CRI: 80 Efficacy: 87,3 lm/w MacAdam: 3 UGR: <19 Power Supply: 220-240V 50/60Hz Type: MID POWER LED Gear: Electronic LED Lifetime: 70.000 L80 B10 (Ta=25°C) Power: 16W

Light output tolerance +/- 10%



FIL35








PHOTOMETRIC DATA:

$$\label{eq:eta-problem} \begin{split} & \text{F31RE112MOOC830NB} \\ & \eta = 99\% \\ & \text{Imax} = 693 \text{ cd/klm} \\ & \text{UTE: 0,99C} \end{split}$$

CIE: 70 93 100 100 99







Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.