FIL35



F31RE112MOOP830NB

- FIL35 REC 1120 2960 WW OPAL BK.

Description:



Finish: Matte black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 1.708 lm
 ⁰K :
 3000

 Plum:
 18W
 CRI :
 80

 Efficacy:
 94,9 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

Electronic

LED Lifetime: 70.000 L80 B10 (Ta=25°C) **Gear:**

Power: 16W

Light output tolerance +/- 10%

EPD

FIL35



FIL35 REC 1120 2960 WW OPAL BK.





PHOTOMETRIC DATA:


 $F31RE112MOOP830NB $$ \eta = 100\% $$ Imax = 389 cd/kIm $$ UTE: 1,00E$

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

Description: F3COX/MMG

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.