## FIL35



## F31RE112MOOP840DG

- FIL35 REC 1120 2960 NW OPAL DALI GR.

Description:



Finish: Gloss grey

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.772 lm
 % :
 4000

 Plum:
 18W
 CRI :
 80

 Efficacy:
 98,4 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 70.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 16W

Light output tolerance +/- 10%

EPD

## FIL35









#### **PHOTOMETRIC DATA:**


 $F31RE112MOOP840DG \\ \eta = 100\% \\ Imax = 389 \ cd/klm \\ UTE: \ 1,00E$ 

CIE: 49 80 97 100 100









## **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.