FIL35



-	4084		
12-1	140M	 PΧΔ	шн


FIL35 REC 1400 3700 NW OPAL DALI BK.

Description: Matte black RAL 9011 Finish: Installation: Recessed **TECHNICAL SPECIFICATIONS:** Light output: 2.215 lm °K: 4000 Plum: 21,2W CRI: 80 Efficacy: 104,5 lm/w MacAdam: 3 Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI Power: 19W Light output tolerance +/- 10%



FIL35









PHOTOMETRIC DATA:


$$\label{eq:eta-problem} \begin{split} &\text{F31RE140MOOP840DB} \\ &\eta = 100\% \\ &\text{Imax} = 389 \text{ cd/klm} \\ &\text{UTE: 1,00E} \end{split}$$

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.