## FIL35



## F31RE140MOOP840NW

- FIL35 REC 1400 3700 NW OPAL WH.

Description:



Finish: Matte white RAL 9010

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.215 lm
 %K:
 4000

 Plum:
 21,2W
 CRI:
 80

 Efficacy:
 104,5 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

Electronic

**LED Lifetime:** 70.000 L80 B10 (Ta=25°C) **Gear:** 


Power: 19W

Light output tolerance +/- 10%

EPD

## FIL35









#### **PHOTOMETRIC DATA:**


 $F31RE140MOOP840NW \\ \eta = 100\% \\ Imax = 389 \ cd/klm \\ UTE: \ 1,00E$ 

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

## **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.