FIL35



F31RE168MOOC840NG

- FIL35 REC 1680 4440 NW OP COMF GR.

Description:



Finish: Gloss grey

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 2.445 lm
 %:
 4000

 Plum:
 25,2W
 CRI:
 80

 Efficacy:
 97 lm/w
 MacAdam:
 3

Power Supply:

Gear:

220-240V 50/60Hz

Electronic

UGR: <19

Type: MID POWER LED

LED Lifetime: 70.000 L80 B10 (Ta=25°C)

Power: 22W


Light output tolerance +/- 10%



Data according to regulations 2019/2020/EU and 2019/2015/EU

FIL35










PHOTOMETRIC DATA:


F31RE168MOOC840NG η = 99% Imax = 693 cd/klm UTE: 0,99C

CIE: 70 93 100 100 99









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.