## FIL35



F31RE196MOOP830DB


- FIL35 REC 1960 5180 WW OPAL DALI BK.

Description:			
Finish: Matte black RAL 9011			
Installation: Recessed			
TECHNICAL SPECIFICATIONS:			
Light output:	2.989 lm	<sup>ο</sup> K :	3000
Plum:	28W	CRI:	80
Efficacy:	106,8 lm/w	MacAdam:	3
Туре:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	25W		
Light output tolerance +/- 10%			



## FIL35









#### **PHOTOMETRIC DATA:**


 $F31RE196MOOP830DB \\ \eta = 100\% \\ Imax = 389 \ cd/klm \\ UTE: \ 1,00E$ 

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

## **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.