FIL35



F31RE196MOOP830DG

- FIL35 REC 1960 5180 WW OPAL DALI GR.

Description:



Finish: Gloss grey

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 2.989 lm
 %:
 3000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 106,8 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 70.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 25W

Light output tolerance +/- 10%

EPD

FIL35




FIL35 REC 1960 5180 WW OPAL DALI GR.





PHOTOMETRIC DATA:


F31RE196MOOP830DG η = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.