## **Product datasheet**

## FIL35



## F31RE196MOOP830NG

- FIL35 REC 1960 5180 WW OPAL GR.

Description:



Finish: Gloss grey

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.989 lm
 %:
 3000

 Plum:
 28W
 CRI:
 80

 Efficacy:
 106,8 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 25W

Light output tolerance +/- 10%



## FIL35




FIL35 REC 1960 5180 WW OPAL GR.





#### **PHOTOMETRIC DATA:**


F31RE196MOOP830NG  $\eta$  = 100% lmax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

## **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.