FIL35



F31RE196MOOP840DB

- FIL35 REC 1960 5180 NW OPAL DALI BK.

Description:				
inish: Matte	black RAL 9011			
nstallation: R	ecessed			
ECHNICAL SP	ECIFICATIONS:			
ight output:	3.101 lm	°K :	4000	
lum:	28W	CRI:	80	
fficacy:	110,8 lm/w	MacAdam:	3	
	MID POWER LED	Power Supply:	220-240V 50/60Hz	
уре:				
ype: ED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI	
	70.000 L80 B10 (Ta=25°C) 25W	Gear:	Adjustable DALI	
ED Lifetime:	·	Gear:	Adjustable DALI	



FIL35



FIL35 REC 1960 5180 NW OPAL DALI BK.





PHOTOMETRIC DATA:


$$\label{eq:eta-parameter} \begin{split} &\text{F31RE196MOOP840DB} \\ &\eta = 100\% \\ &\text{Imax} = 389 \text{ cd/klm} \\ &\text{UTE: 1,00E} \end{split}$$

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.