FIL35



F31RE196MOOP840DG

- FIL35 REC 1960 5180 NW OPAL DALI GR.

Description:



Finish: Gloss grey

Installation: Recessed

TECHNICAL SPECIFICATIONS:

 Light output:
 3.101 lm
 % :
 4000

 Plum:
 28W
 CRI :
 80

 Efficacy:
 110,8 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 70.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI


Power: 25W

Light output tolerance +/- 10%



FIL35










PHOTOMETRIC DATA:


$$\label{eq:eta-poly-state} \begin{split} &\text{F31RE196MOOP840DG} \\ &\eta = 100\% \\ &\text{Imax} = 389 \text{ cd/klm} \\ &\text{UTE: } 1,00\text{E} \end{split}$$

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.