### **Product datasheet**

# FIL35



E24D	E224M		0.40	
FOIR	CZZ4IVI	UUP	04U	UU

- FIL35 REC 2240 5920 NW OPAL DALI GR.

Description:					
Finish: Gloss grey					
Installation: Recessed					
TECHNICAL SPECIFICATIONS:					
Light output:	3.544 lm	°K:	4000		
Plum:	36W	CRI:	80		
Efficacy:	98,4 lm/w	MacAdam:	3		
Type:	MID POWER LED	Power Supply:	220-240V 50/60Hz		
LED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI		
Power:	32W				
Light output tolerance +/- 10%					



### FIL35







FIL35 REC 2240 5920 NW OPAL DALI GR.


#### **PHOTOMETRIC DATA:**


 $F31RE224MOOP840DG $$\eta = 100\%$$Imax = 389 cd/klm$$UTE: 1,00E$ 

CIE: 49 80 97 100 100









### **Product datasheet**

### FIL35



## ACCESORIES:

## Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.