FIL35



E24D	E224M		840DW
FOIR	CZZ4IV	IUUP	04UUYY


- FIL35 REC 2240 5920 NW OPAL DALI WH.

Description: Matte white RAL 9010 Finish: Installation: Recessed **TECHNICAL SPECIFICATIONS:** Light output: 3.544 lm °K: 4000 Plum: 36W CRI: 80 Efficacy: 98,4 lm/w MacAdam: 3 Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI Power: 32W Light output tolerance +/- 10%



FIL35










PHOTOMETRIC DATA:


F31RE224MOOP840DW η = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.