Product datasheet

FIL35



F31SF084MOOP830DG

- FIL35 SUR 840 2220 WW OPAL DALI GR.

Description:



Finish: Gloss grey

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.281 lm
 % :
 3000

 Plum:
 13,5W
 CRI :
 80

 Efficacy:
 94,9 lm/w
 MacAdam:
 3

 Type:
 MID POWER LED
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 70.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 12W

Light output tolerance +/- 10%



FIL35






FIL35 SUR 840 2220 WW OPAL DALI GR.


PHOTOMETRIC DATA:


F31SF084MOOP830DG η = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support

F3FX50G



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.