Product datasheet

FIL35



F31SF084MOOP840NG

- FIL35 SUR 840 2220 NW OPAL GR.

Description:



Finish: Gloss grey

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 1.329 lm
 %:
 4000

 Plum:
 13,5W
 CRI:
 80

 Efficacy:
 98,4 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

Electronic

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear:


Power: 12W

Light output tolerance +/- 10%

EPD

FIL35









PHOTOMETRIC DATA:


F31SF084MOOP840NG η = 100% lmax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support

F3FX50G



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.