### FIL35



F31SF112MOOP830DW

- FIL35 SUR 1120 2960 WW OPAL DALI WH.

Description:				
Finish: Matte	white RAL 9010			
nstallation: S	urface			
ECHNICAL SP	ECIFICATIONS:			
ight output:	1.708 lm	ºK :	3000	
Plum:	18W	CRI:	80	
Efficacy:	94,9 lm/w	MacAdam:	3	
Гуре:	MID POWER LED	Power Supply:	220-240V 50/60Hz	
_ED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI	
Power:	16W			
Light output toler	rance ±/- 10%			
igni output tolel	diloc 17 10/0			



## F31SF112MOOP830DW





FIL35 SUR 1120 2960 WW OPAL DALI WH.


#### **PHOTOMETRIC DATA:**


F31SF112MOOP830DW  $\eta$  = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









#### **Product datasheet**

### FIL35



ACCESORIES:

### **Assembly**



Product code:

Description: F3COX/MMB

FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

# **ACCESORIES:**

## Support

F3FX50G



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.