FIL35



		P830	

- FIL35 SUR 1120 2960 WW OPAL BK.

Description: Finish: Matte black RAL 9011 Installation: Surface **TECHNICAL SPECIFICATIONS:** Light output: 1.708 lm °K: 3000 Plum: 18W CRI: 80 Efficacy: 94,9 lm/w MacAdam: 3 Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic Power: 16W

Light output tolerance +/- 10%



FIL35










PHOTOMETRIC DATA:


$$\label{eq:eta-problem} \begin{split} &\text{F31SF112MOOP830NB} \\ &\eta = 100\% \\ &\text{Imax} = 389 \text{ cd/klm} \\ &\text{UTE: 1,00E} \end{split}$$

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

Description: F3COX/MMB

FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support

F3FX50G



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.