


F31SF112MOOP840DW


- FIL35 SUR 1120 2960 NW OPAL DALI WH.

Description:**Finish:** Matte white RAL 9010**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

Light output:	1.772 lm	°K :	4000
Plum:	18W	CRI :	80
Efficacy:	98,4 lm/w	MacAdam:	3
Type:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	16W		

Light output tolerance +/- 10%

PHOTOMETRIC DATA :



ACCESORIES :

Assembly



Product code:
F3COX/MMB

Description:
FIL 35 ACC. COVER X/MM BK.



Product code:
F3COX/MMG

Description:
FIL 35 ACC. COVER X/MM GR.



Product code:
F3COX/MMW

Description:
FIL 35 ACC. COVER X/MM WH.



Product code:
F3FX50B

Description:
ACC. WALL BRACKET FIL45 50MM BK.



Product code:
F3FX50G

Description:
ACC. WALL BRACKET FIL35 50MM GR.



Product code:
F3FX50W

Description:
ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES :

Support



Product code:
F3FX15G

Description:
ACC. CEILING BRACKET FIL35 15MM GR.