## **Product datasheet**

## FIL35



## F31SF112MOOP840NG

- FIL35 SUR 1120 2960 NW OPAL GR.

Description:



Finish: Gloss grey

Installation: Surface

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.772 lm
 ⁰K:
 4000

 Plum:
 18W
 CRI:
 80

 Efficacy:
 98,4 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic


Power: 16W

Light output tolerance +/- 10%

EPD

## FIL35










#### **PHOTOMETRIC DATA:**


F31SF112MOOP840NG  $\eta$  = 100% lmax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









#### **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

# ACCESORIES:

# Support

F3FX50G



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.