Product datasheet

FIL35



F31SF140MOOC830NG

- FIL35 SUR 1400 3700 WW OP COMF GR.

Description:			
Finish: Gloss grey			
Installation: Surface			
TECHNICAL SPECIFICATIONS:			
Light output:	1.964 lm	°K :	3000
Plum:	21,2W	CRI:	80
Efficacy:	92,7 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Туре:	MID POWER LED	Gear:	Electronic
LED Lifetime:	70.000 L80 B10 (Ta=25°C)		
Power:	19W		
Light output tolerance +/- 10%			



FIL35





FIL35 SUR 1400 3700 WW OP COMF GR.




PHOTOMETRIC DATA:

F31SF140MOOC830NG η = 99% lmax = 693 cd/klm UTE: 0,99C CIE: 70 93 100 100 99







Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

Description: F3COX/MMB

FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support

F3FX50G



Product code:

Description:

F3FX15G ACC. CEILING BRACKET FIL35 15MM GR.