## **Product datasheet**

## FIL35



## F31SF140MOOP840NB

- FIL35 SUR 1400 3700 NW OPAL BK.

Description:



Finish: Matte black RAL 9011

Installation: Surface

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 2.215 lm
 ⁰K :
 4000

 Plum:
 21,2W
 CRI :
 80

 Efficacy:
 104,5 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

Gear:

Electronic

**LED Lifetime:** 70.000 L80 B10 (Ta=25°C)


Power: 19W

Light output tolerance +/- 10%

EPD

## FIL35









#### **PHOTOMETRIC DATA:**


F31SF140MOOP840NB  $\eta$  = 100% Imax = 389 cd/klm UTE: 1,00E

CIE: 49 80 97 100 100









#### **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

# ACCESORIES:

# Support

F3FX50G



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.