Product datasheet

FIL35



F31SF140MOOP840NG

- FIL35 SUR 1400 3700 NW OPAL GR.

Description:



Finish: Gloss grey

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 2.215 lm
 ⁰K :
 4000

 Plum:
 21,2W
 CRI :
 80

 Efficacy:
 104,5 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 19W

Light output tolerance +/- 10%

EPD

FIL35




FIL35 SUR 1400 3700 NW OPAL GR.





PHOTOMETRIC DATA:


F31SF140MOOP840NG $\eta = 100\%$ $lmax = 389 \ cd/klm$ $UTE: \ 1,00E$

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support

F3FX50G



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.