

F31SF224MOOP830NG

- FIL35 SUR 2240 5920 WW OPAL GR.

Description:

Finish: Gloss grey

Installation: Surface


TECHNICAL SPECIFICATIONS:

Light output:	3.416 lm	°K :	3000
Plum:	32,5W	CRI :	80
Efficacy:	96,7 lm/w	MacAdam:	3
Type:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	70.000 L80 B10 (Ta=25°C)	Gear:	Electronic
Power:	30,2W		

Light output tolerance +/- 10%



PHOTOMETRIC DATA :



ACCESORIES :

Assembly




Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.




Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

F3FX50G

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES :

Support



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.