Product datasheet

FIL35



F31SF224MOOP840NB

- FIL35 SUR 2240 5920 NW OPAL BK.

Description:



Finish: Matte black RAL 9011

Installation: Surface

TECHNICAL SPECIFICATIONS:

 Light output:
 3.544 lm
 %:
 4000

 Plum:
 32,5W
 CRI:
 80

 Efficacy:
 96,7 lm/w
 MacAdam:
 3

Type: MID POWER LED Power Supply: 220-240V 50/60Hz

LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Electronic

Power: 30,2W

Light output tolerance +/- 10%



FIL35







FIL35 SUR 2240 5920 NW OPAL BK.


PHOTOMETRIC DATA:


$$\label{eq:f31SF224MOOP840NB} \begin{split} \eta &= 100\% \\ \text{Imax} &= 389 \text{ cd/klm} \\ \text{UTE: } 1,00\text{E} \end{split}$$

CIE: 49 80 97 100 100









Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB



FIL 35 ACC. COVER X/MM BK.



Product code:

F3COX/MMG



FIL 35 ACC. COVER X/MM GR.



Product code: F3COX/MMW

Description:

FIL 35 ACC. COVER X/MM WH.



Product code:

F3FX50B

Description:

ACC. WALL BRACKET FIL45 50MM BK.



Product code:

Description:

ACC. WALL BRACKET FIL35 50MM GR.



Product code:

F3FX50W

Description:

ACC. WALL BRACKET FIL35 50MM WH.

ACCESORIES:

Support

F3FX50G



Product code:

F3FX15G

Description:

ACC. CEILING BRACKET FIL35 15MM GR.