## **Product datasheet**

## FIL35



E247		0.484	100	CO 4	ONIVA
F31	ıκι	184IV	IUU	<b>L84</b>	ONW

- FIL35 TRIM 840 2220 NW OP COMF WH.

Description:

Finish: Matte white RAL 9010

Power Supply:

Gear:

220-240V 50/60Hz

Electronic

## **TECHNICAL SPECIFICATIONS:**

 Light output:
 1.223 lm
 %K:
 4000

 Plum:
 13,5W
 CRI:
 80

 Efficacy:
 90,6 lm/w
 MacAdam:
 3

**UGR:** <19

Type: MID POWER LED

**LED Lifetime:** 70.000 L80 B10 (Ta=25°C)


Power: 12W

Light output tolerance +/- 10%



## FIL35










#### **PHOTOMETRIC DATA:**

F31TR084MOOC840NW η = 99% Imax = 693 cd/klm UTE: 0,99C CIE: 70 93 100 100 99







Data according to regulations 2019/2020/EU and 2019/2015/EU

## **Product datasheet**

## FIL35



# ACCESORIES:

# Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.