Product datasheet

FIL35



F31TR168MOOP840DW

-	FIL35	TRIM	1680	4440	NW	OPAL	DALI	WH.
---	-------	------	------	------	----	-------------	------	-----

Description: Finish: Matte white RAL 9010 **TECHNICAL SPECIFICATIONS:** Light output: 2.658 lm °K: 4000 Plum: 25,2W CRI: 80 Efficacy: 105,5 lm/w MacAdam: 3 Type: MID POWER LED Power Supply: 220-240V 50/60Hz LED Lifetime: 70.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI Power: 22W

Light output tolerance +/- 10%



FIL35










PHOTOMETRIC DATA:


$$\label{eq:eta-problem} \begin{split} &\text{F31TR168MOOP840DW} \\ &\eta = 100\% \\ &\text{Imax} = 389 \text{ cd/kIm} \\ &\text{UTE: 1,00E} \end{split}$$

CIE: 49 80 97 100 100









Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL35



ACCESORIES:

Assembly



Product code:

F3COX/MMB

Description:

FIL 35 ACC. COVER X/MM BK.

Product code:

F3COX/MMG

Description:

FIL 35 ACC. COVER X/MM GR.



Product code:

Description:

F3COX/MMW FIL 35 ACC. COVER X/MM WH.