Product datasheet

FIL45

F42RE140MOTE930DB



FIL45 G2 REC 1400 2800 9WW TECH DALI BK

Description:

LAMP recessed structure FIL45 G2 REC 1400. Manufactured from extruded aluminum with an 80% recycling rate, optic and black mat polycarbonate reflector TECH ULTRACONFORT to control light distribution and reduce glare UGR <15. Model for LED MID-POWER, colour temperature 3000K and IRC90. Electronic DALI gear included. IP20, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED life time: 90.000 L80 B10. Available finishes: White, black and grey. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Matte black RAL 9011 Dimensions: 1.398 x 55 x 76 mm

Weight: 3.410 g

Installation: Recessed

1,406 x 51 x 0 mm Recessing measures:

TECHNICAL SPECIFICATIONS:

Light output: 2.183 lm °K: 3000 Plum: 19W CRI: 90 Efficacy: 114,9 lm/w 71 R9: UGR: <15 MacAdam: 3

Type: MID POWER Power Supply: 220-240V 50/60Hz LED Lifetime: 90.000 L80 B10 (Ta=25°C) Gear: Adjustable DALI

17W Power:

Light output tolerance +/- 10%



CLASE

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU













F42RE140MOTE930DB





FIL45 G2 REC 1400 2800 9WW TECH DALI BK


PHOTOMETRIC DATA:


F42RE140MOTE930DB η = 100% Imax = 906 cd/klm UTE: 1,00A

CIE: 92 100 100 100 100









F42SF168MOTA930DG


 $\eta = 100\%$


lmax = 1070 cd/klm


UTE: 1,00A

CIE: 85 100 100 100 100









Product datasheet

FIL45



ACCESORIES:

Assembly



Product code:

F42JO



FIL45 ACC. SU/RE INTM JOINT B



Product code:

F4COX/MMB



FIL 45 ACC. COVER X/MM BK.



Product code:

F4COX/MMG

Description:

FIL 45 ACC. COVER X/MM GR.



Product code:

F4COX/MMW

Description:

FIL 45 ACC. COVER X/MM WH.



Product code:

F4PRREX/MMB

Description:

FIL 45 ACC. REC PROFIL X/MM BK.



Product code:

F4PRREX/MMG

Description:

FIL 45 ACC. REC PROFIL X/MM GR.



Product code:

F4PRREX/MMW

Description:

FIL 45 ACC. REC PROFIL X/MM WH.



Product code:

F4REECB

Description:

FIL45 ACC. REC END COVER BK.



Product code:

F4REECG

Description:

FIL45 ACC. REC END COVER GR.



Product code:

F4REECW

Description:

FIL45 ACC. REC END COVER WH.

Data according to regulations 2019/2020/EU and 2019/2015/EU

Product datasheet

FIL45





Description: Product code:

F4TORFG FIL45 ACC. TOOL REMOVE REFLECTOR

ACCESORIES:

Optical



Product code: Description:

F4DIX/MMOP FIL 45 ACC. OPAL DIFFUSER X/MM

ACCESORIES:

Adjustment and control



Product code: F41EMG3HDWB Description:

ACC.FIL45 DOWNLIGHT EMERGENCIA 3H BK



Product code: F41EMG3HDWG Description:

ACC.FIL45 DOWNLIGHT EMERGENCIA 3H GR



Product code: F41EMG3HDWW Description:

ACC.FIL45 DOWNLIGHT EMERGENCIA 3H WH



Product code: F41LIGHTSNDB Description:

ACC.FIL45 SENSOR BASIC ILD DALI-2 BK



Product code:

Description: F41LIGHTSNDG

ACC.FIL45 SENSOR BASIC ILD DALI-2 GR

Product code: F41LIGHTSNDW Description:

ACC.FIL45 SENSOR BASIC ILD DALI-2 WH

Data according to regulations 2019/2020/EU and 2019/2015/EU