



F51SL112MOOC830NB

**FIL50 SLIM 1140 2600 WW COMF BK****Description:**

LAMP suspended or surface mounted structure FIL 50 SLIM 1120 2600. Manufactured from extruded aluminum with an 80% recycling rate, with an OPAL CONFORT diffuser made of a translucent polycarbonate diffuser and an optical film to achieve a controlled light distribution and low glare level, less than UGR 19. Model for LED MID-POWER, colour temperature 3000K and CRI80. Electronic ON OFF gear included. IP20 and IK07 ratings. Insulation Class II. Photobiological safety group 0. LED life time: 50.000 L90 B10 Available finishes: White and black.

**Finish:** Matte black RAL 9011**Dimensions:** 1.140 x 50 x 30 mm**Installation:** Surface**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	1.922 lm	<b>°K :</b>	3000
<b>Plum:</b>	20,9W	<b>CRI :</b>	80
<b>Efficacy:</b>	92 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	MID POWER	<b>Gear:</b>	Electronic
<b>LED Lifetime:</b>	50.000 L90 B10 (Ta=25°C)		
<b>Power:</b>	18W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

PHOTOMETRIC DATA :

