


F53RE112HOOP830DG



- **FIL50 G3 REC 1120 6200 WW OPAL DALI GR**

Description:

LAMP recessed structure FIL 50 REC 1120. Manufactured from extruded recycled aluminum with a rate of 80%, with opal polycarbonate diffuser. Model for LED MID-POWER, colour temperature 3000K with CRI80 and DALI electronic gear included. IP43, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED lifetime: 72.000 L80 B10. White and grey finishes available. Environmental Product Declaration - EPD®available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.



Finish: Gloss grey

Dimensions: 1.123 x 66 x 67 mm

Weight: 2.166 g


Installation: Recessed

Recessing measures: 1,133 x 52 x 80 mm

TECHNICAL SPECIFICATIONS:

Light output:	3.846 lm	°K :	3000
Plum:	40,10W	CRI :	80
Efficacy:	95,9 lm/w	MacAdam:	3
Type:	MID POWER LED	Power Supply:	220-240V 50/60Hz
LED Lifetime:	72.000 L80 B10 (Ta=25°C)	Gear:	Adjustable DALI
Power:	35.8W		

Light output tolerance +/- 10%







CUSTOM MADE OPTIONS:



PHOTOMETRIC DATA :

F53RE112HOOP830DG
 $\eta = 100\%$
 $I_{max} = 414 \text{ cd/klm}$
UTE: 1,00D
CIE: 53 85 98 100 100



ACCESSORIES :

Assembly



Product code:

ELWRST

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

F5COX/MMG

F5COX/MMW

F5PREX/MMG

F5PREX/MMW

Description:

FIL 50 ACC. COVER X/MM GR.

FIL 50 ACC. COVER X/MM WH.

FIL 50 ACC. REC PROFIL X/MM GR.

FIL 50 ACC. REC PROFIL X/MM WH.



Product code:

F5DIX/MMOP

Description:

FIL 50 ACC. OPAL DIFFUSER X/MM




Product code:

F5JO

Description:

ACC. INTM JOINT B



Product code:


F5REECG

F5REECW

Description:

FIL 50 ACC. REC END COVER GR.

FIL 50 ACC. REC END COVER WH.



Product code:

F5REHCG

F5REHCW

Description:

FIL 50 ACC. REC 90° CORNER GR.

FIL 50 ACC. REC 90° CORNER WH.