


## F53RE168HOPR840NG



## - FIL50 G3 REC 1680 9300 NW PRISM GR

**Description:**


LAMP recessed structure FIL 50 REC 1680. Manufactured from extruded recycled aluminum with a rate of 80%, with prismatic diffuser polycarbonate to control light distribution and reduce glare UGR<19. Model for MID-POWER LED, neutral white colour temperature and control gear included. With a IP43, IK07 protection rating. Insulation class I. Photobiological safety group 0. LED lifetime: 72.000 L80 B10. White and grey finishes available. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

**Finish:** Gloss grey**Dimensions:** 1.683 x 66 x 67 mm**Weight:** 2.860 g**Installation:** Recessed**Recessing measures:** 1,693 x 52 x 80 mm**TECHNICAL SPECIFICATIONS:**

<b>Light output:</b>	6.990 lm	<b>°K :</b>	4000
<b>Plum:</b>	59,10W	<b>CRI :</b>	80
<b>Efficacy:</b>	118,3 lm/w	<b>MacAdam:</b>	3
<b>UGR:</b>	<19	<b>Power Supply:</b>	220-240V 50/60Hz
<b>Type:</b>	MID POWER LED	<b>Gear:</b>	Electronic
<b>LED Lifetime:</b>	72.000 L80 B10 (Ta=25°C)		
<b>Power:</b>	53.7W		

**Light output tolerance +/- 10%****CUSTOM MADE OPTIONS:**

PHOTOMETRIC DATA :



ACCESORIES :

Assembly



**Product code:**  
ELWRST

**Description:**  
ACC. ELECTROSTATICS WRIST STRAP




**Product code:**  
F5COX/MMG  
F5COX/MMW  
F5PRREX/MMG  
F5PRREX/MMW

**Description:**  
FIL 50 ACC. COVER X/MM GR.  
FIL 50 ACC. COVER X/MM WH.  
FIL 50 ACC. REC PROFIL X/MM GR.  
FIL 50 ACC. REC PROFIL X/MM WH.



**Product code:**  
F5JO

**Description:**  
ACC. INTM JOINT B



**Product code:**  
F5REECG  
F5REECW

**Description:**  
FIL 50 ACC. REC END COVER GR.  
FIL 50 ACC. REC END COVER WH.



**Product code:**  
F5REHCG  
F5REHCW

**Description:**  
FIL 50 ACC. REC 90° CORNER GR.  
FIL 50 ACC. REC 90° CORNER WH.