


F53RE168MOPR830DW




FIL 50 G3 REC 1680 3900 WW PRISM DALI WH

Description:


LAMP recessed structure FIL 50 REC 1680. Manufactured from extruded recycled aluminum with a rate of 80%, with prismatic diffuser polycarbonate to control light distribution and reduce glare UGR<19. Model for LED MID-POWER, colour temperature 3000K with CRI80 and DALI electronic gear included. IP43, IK07 ratings. Insulation Class I. Photobiological safety group 0. LED lifetime: 72.000 L80 B10. White and grey finishes available. Environmental Product Declaration - EPD@available, according to UNE-EN ISO 9001:2015 and UNE-EN ISO 14001:2015.

Finish: Matte white RAL 9010**Dimensions:** 1.683 x 66 x 67 mm**Weight:** 2.860 g**Installation:** Recessed**Recessing measures:** 1,693 x 52 x 80 mm**TECHNICAL SPECIFICATIONS:**

Light output:	3.473 lm	°K :	3000
Plum:	31,20W	CRI :	80
Efficacy:	111,3 lm/w	MacAdam:	3
UGR:	<19	Power Supply:	220-240V 50/60Hz
Type:	MID POWER LED	Gear:	Adjustable DALI
LED Lifetime:	72.000 L80 B10 (Ta=25°C)		
Power:	26.8W		

Light output tolerance +/- 10%**CUSTOM MADE OPTIONS:**

PHOTOMETRIC DATA :



ACCESORIES :

Assembly




Product code:

ELWRST

Description:

ACC. ELECTROSTATICS WRIST STRAP



Product code:

F5COX/MMG

F5COX/MMW

F5PRREX/MMG

F5PRREX/MMW

Description:

FIL 50 ACC. COVER X/MM GR.

FIL 50 ACC. COVER X/MM WH.

FIL 50 ACC. REC PROFIL X/MM GR.

FIL 50 ACC. REC PROFIL X/MM WH.




Product code:

F5JO

Description:

ACC. INTM JOINT B



Product code:


F5REECG

F5REECW

Description:

FIL 50 ACC. REC END COVER GR.

FIL 50 ACC. REC END COVER WH.



Product code:

F5REHCG

F5REHCW

Description:

FIL 50 ACC. REC 90° CORNER GR.

FIL 50 ACC. REC 90° CORNER WH.