HANCE DOWNLIGHT



HD2RE07SS930NB



HANCE G2 DOWN REC 700 9WW SSP BK

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 700. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 10° super spot polycarbonate optics. LED HIGH POWER, 3000K and CRI90. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 60.000 L90B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 438 lm °K: 3000 Plum: 8,6W CRI: 90 Efficacy: 51 lm/w R9: 53 UGR: <16 MacAdam: 3

Type: HIGH POWER Power Supply: 220-240V 50/60Hz

LED Lifetime: 60.000 L90B10 (Ta=25°C) Gear: Electronic

Power: 7W

Light output tolerance +/- 10%























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU



















HANCE DOWNLIGHT




HD2RE07SS930NB


HANCE G2 DOWN REC 700 9WW SSP BK


PHOTOMETRIC DATA:


HD2RE10SS930NB η = 99% Imax = 20858 cd/klm UTE:


CIE: 103 100 100 100 99




















HANCE DOWNLIGHT



ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65B

Description:

HANCE 1000/2000 ACC. RING DECO BK.



Product code:

HSRI65C

Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

e:

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS