HANCE DOWNLIGHT


HD2RE40FL940NB



HANCE G2 DOWN REC 4000 9NW FL BK

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35º flood reflector. LED COB, 4000K and CRI90. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.800 lm °K: 4000 Plum: 36,7W CRI: 90 Efficacy: 103,5 lm/w R9: 64 Type: СОВ MacAdam: 3

LED Lifetime: 72.000 L80B10 (Ta=25°C) Power Supply: 220-240V 50/60Hz

33W Gear: Power: Electronic

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU

















HANCE DOWNLIGHT



HD2RE40FL940NB


HANCE G2 DOWN REC 4000 9NW FL BK


90°


PHOTOMETRIC DATA:


HD2RE40FL940NB η = 100% Imax = 2005 cd/klm UTE: CIE: 100 100 100 100 10


CIE: 100 100 100 100 100

















Data according to regulations 2019/2020/EU and 2019/2015/EU