HANCE DOWNLIGHT




HD2RE40MF830DB



HANCE G2 DOWN REC 4000 WW MFL DALI BK

Description:

LAMP multidirectional recessed downlight HANCE G2 DOWN REC 4000. Allowing 355° rotation and tilting up to 30°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 3000K and CRI80. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 4.343 lm °K: 3000 Plum: 36,7W CRI: 80 Efficacy: 118,3 lm/w R9: 61 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 33W

Light output tolerance +/- 10%

























CUSTOM MADE OPTIONS:

























HANCE DOWNLIGHT





HD2RE40MF830DB


HANCE G2 DOWN REC 4000 WW MFL DALI BK

PHOTOMETRIC DATA:

HD2RE40MF830DB η = 100% Imax = 3926 cd/klm UTE: CIE: 101 100 100 100 100







HANCE DOWNLIGHT



ACCESORIES:

Optical



Product code:

HS2HO75



Product code:

HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE HS2RI90C



HANCE G2 3000/4000 ACC. RING DECO CO.



Product code:

HS2RI90M



HANCE G2 3000/4000 ACC. RING DECO MET.

Product code:

HS2RI90W

Description:

HANCE G2 3000/4000 ACC. RING DECO WH.



Product code:

Description:

Description:

HS2TR75 HANCE G2 3000/4000 ACC. DIF TRANS