### HANCE DOWNLIGHT



### HD2SR10MF940DB



### HANCE G2 DOWN SEMIREC 1000 9NW MFL DA BK

### Description:

LAMP multidirectional semi-recessed downlight HANCE G2 DOWN SEMIREC 1000. Allowing 355° rotation and tilting up to 85°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 25° middle flood reflector. LED COB, 4000K and CRI90. Electronic DALI control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 78.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Recessed

### **TECHNICAL SPECIFICATIONS:**

Light output: 924 lm °K: 4000 Plum: 8,6W CRI: 90 Efficacy: 107,4 lm/w R9: 66 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 78.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 7W

## Light output tolerance +/- 10%























# **CUSTOM MADE OPTIONS:**









Data according to regulations 2019/2020/EU and 2019/2015/EU

















### HANCE DOWNLIGHT




HD2SR10MF940DB


# HANCE G2 DOWN SEMIREC 1000 9NW MFL DA BK


## **PHOTOMETRIC DATA:**


HD2SR10MF940DB  $_{\eta}$  = 100% Imax = 3354 cd/klm UTE:


CIE: 101 100 100 100 100

















Data according to regulations 2019/2020/EU and 2019/2015/EU

# **HANCE DOWNLIGHT**



# ACCESORIES:

# Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65B

### Description:

HANCE 1000/2000 ACC. RING DECO BK.



Product code:

HSRI65C

# Description:

HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

# Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

e:

# Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS