## HANCE DOWNLIGHT


## HD2SR40SP830NW



## HANCE G2 DOWN SEMIREC 4000 WW SP WH

## Description:

LAMP multidirectional semi-recessed downlight HANCE G2 DOWN SEMIREC 4000. Allowing 355° rotation and tilting up to 85°. Body and frame made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 3000K and CRI80. Electronic ON OFF control gear included. IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised white RAL 9010

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 4.440 lm °K: 3000 Plum: 36,7W CRI: 80 Efficacy: 121 lm/w R9: 61 UGR: <19 MacAdam: 3

Type: COB Power Supply: 220-240V 50/60Hz

LED Lifetime: 72.000 L80B10 (Ta=25°C) Gear: Electronic

33W Power:

## Light output tolerance +/- 10%

























## **CUSTOM MADE OPTIONS:**











Data according to regulations 2019/2020/EU and 2019/2015/EU


















## HANCE DOWNLIGHT





HD2SR40SP830NW


## HANCE G2 DOWN SEMIREC 4000 WW SP WH

## **PHOTOMETRIC DATA:**









## HANCE DOWNLIGHT



# ACCESORIES:

## Optical



Product code:

HS2HO75



Product code:

HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE HS2RI90C



HANCE G2 3000/4000 ACC. RING DECO CO.



Product code:

HS2RI90M



Description:

HANCE G2 3000/4000 ACC. RING DECO MET.



Product code:

HS2RI90W

Description:

HANCE G2 3000/4000 ACC. RING DECO WH.



Product code:

Description:

HS2TR75 HANCE G2 3000/4000 ACC. DIF TRANS