Worktitude for light


HS2SR20FL830NB



HANCE G2 SEMIREC 2000 WW FL BK

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 2000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 35° flood reflector. LED COB, 3000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output: 2.238 lm °K: 3000 Plum: 20,8W CRI: 80 Efficacy: 107,6 lm/w R9: 60 Type: СОВ MacAdam: 3

LED Lifetime: 72.000 L80B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 18W Gear: Electronic

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:

























HS2SR20FL830NB


HANCE G2 SEMIREC 2000 WW FL BK

PHOTOMETRIC DATA:

HS2SR20FL830NB η = 100% Imax = 2218 cd/klm UTE: CIE: 100 100 100 100 100









ACCESORIES:

Optical



Product code:

HSCU50



HANCE 1000/2000 ACC. CUTTING BEAM



Product code:

HSHO50



HANCE 1000/2000 ACC. HONEYCOMB GRILLE



Product code:

HSRI65C



HANCE 1000/2000 ACC. RING DECO CO.



Product code:

HSRI65M

Description:

HANCE 1000/2000 ACC. RING DECO MET.



Product code:

HSRI65W

Description:

HANCE 1000/2000 ACC. RING DECO WH.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS



Product code:

Description:

HSTR50 HANCE 1000/2000 ACC. DIF TRANS