


HS2SR30SP830DB



HANCE G2 SEMIREC 3000 WW SP DALI BK

Description:

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 3000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 3000K and CRI80. Electronic DALI control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

TECHNICAL SPECIFICATIONS:

Light output: 3.233 Im °K: 3000 Plum: 28,3W CRI: 80 Efficacy: 114,2 lm/w R9: 61 UGR: <19 MacAdam: 3

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 72.000 L80B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 25W

Light output tolerance +/- 10%





















CUSTOM MADE OPTIONS:









Data according to regulations 2019/2020/EU and 2019/2015/EU


















HANCE G2 SEMIREC 3000 WW SP DALI BK

PHOTOMETRIC DATA:

HS2SR30SP830DB η = 100% Imax = 5192 cd/klm UTE: CIE: 102 100 100 100 100









ACCESORIES:

Optical



Product code:

HS2HO75



Product code:

HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE HS2RI90C



HANCE G2 3000/4000 ACC. RING DECO CO.



Product code:

HS2RI90M



Product code:

HS2RI90W

Description:

HANCE G2 3000/4000 ACC. RING DECO WH.



Product code:

HS2TR75



Description:

Description:

HANCE G2 3000/4000 ACC. DIF TRANS

HANCE G2 3000/4000 ACC. RING DECO MET.



Product code:

HSSL50

Description:

HANCE 1000/2000 ACC. SOFT LENS