


#### HS2SR30SP840NB



# HANCE G2 SEMIREC 3000 NW SP BK

#### **Description:**

LAMP semi-recessed multidirectional spotlight HANCE G2 SEMIREC 3000. Allowing 355° rotation and tilting up to 90°. Body made of die-cast aluminium for proper thermal management. Black polycarbonate injection moulded anti-glare ring. 20° spot reflector. LED COB, 4000K y CRI80. Electronic ON OFF control gear included.IP20, IK07 ratings. Insulation Class II. LED life time: 72.000 L80B10 (Ta=25°C). Available finishes: Textured white and textured black.



Finish: Texturised black RAL 9011

Installation: Semi-Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output:	3.419 lm	<b>°K</b> :	4000	
Plum:	28,3W	CRI :	80	
Efficacy:	120,8 lm/w	R9 :	64	
UGR:	<19	MacAdam:	3	
Туре:	COB	Power Supply:	220-240V 50/60Hz	
LED Lifetime:	72.000 L80B10 (Ta=25°C)	Gear:	Electronic	
Power:	25W			

#### Light output tolerance +/- 10%



## **CUSTOM MADE OPTIONS:**





HS2SR30SP840NB

HANCE G2 SEMIREC 3000 NW SP BK

# PHOTOMETRIC DATA :

HS2SR30SP840NB	180°	alpha = 19,6°	100%	BACK	FRONT
η = 100%		$\land$	75%	49,9 %	49,9 %
Imax = 5192 cd/klm UTE:			50%		
CIE: 102 100 100 100 100	90° 90°		25%		
	0°			-8H -4H	0H 4H 8H



# ACCESORIES :

### Optical



Product code: HS2HO75

**Description:** HANCE G2 3000/4000 ACC. HONEYCOMB GRILLE HS2RI90C



Product code:

Description: HANCE G2 3000/4000 ACC. RING DECO CO.



Product code:

HS2RI90M

Description: HANCE G2 3000/4000 ACC. RING DECO MET.



Product code: HS2RI90W

Description: HANCE G2 3000/4000 ACC. RING DECO WH.



Product code: HS2TR75





Product code: HSSL50

Description: HANCE 1000/2000 ACC. SOFT LENS