## **KOMBIC 100 DOWNLIGHT**



K11RD2023RF830DBW

- KOMBIC 100 RD 2000 IP23 WW RF FL DA B/W

Description:

Finish: Matte black RAL 9011

Weight: 382 g

Installation: Recessed

## **TECHNICAL SPECIFICATIONS:**

Light output: 1.549 lm °K: 3000 Plum: 14,2W CRI: 80 Efficacy: 109 lm/w R9: 80 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

IP 20 INT 23 EXT

EPD

## **KOMBIC 100 DOWNLIGHT**



K11RD2023RF830DBW

KOMBIC 100 RD 2000 IP23 WW RF FL DA B/W

## **PHOTOMETRIC DATA:**

$$\label{eq:continuous} \begin{split} \text{K11RD2023RF830DBW} \\ \eta &= 100\% \\ \text{Imax} &= 2279 \text{ cd/klm} \\ \text{UTE:} \\ \text{CIE:} \ 100 \ 100 \ 100 \ 100 \ 100 \ 100 \end{split}$$





