Product datasheet

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11RD2023RF840DBB — **KOMBIC 100 RD 2000 IP23 NW RF FL DA B/B**

Description:

Finish: Matte black RAL 9011

Weight: 382 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output:	1.226 lm	**ºK :**	4000
Plum:	14,2W	**CRI :**	80
Efficacy:	86,3 lm/w	**R9 :**	80
UGR:	<19	**MacAdam:**	3
Type:	COB	**Power Supply:**	220-240V 50/60Hz
LED Lifetime:	50.000 L80 B10 (Ta=25ºC)	**Gear:**	Adjustable DALI
Power:	13W		

Light output tolerance +/- 10%

IP
20 INT
23 EXT

EPD

04-02-2025

KOMBIC 100 DOWNLIGHT

LAMP
Worktitude for light

K11RD2023RF840DBB   **KOMBIC 100 RD 2000 IP23 NW RF FL DA B/B**

PHOTOMETRIC DATA :

K11RD2023RF840DBB

η = 100%

Imax = 2279 cd/klm

UTE:

CIE: 100 100 100 100 100

180°

90°   90°

0°

alpha = 33,1º

100%
75%
50%
25%

BACK   FRONT

50,0 %   50,0 %

-8H   -4H   0H   4H   8H