KOMBIC 100 SURFACE



K11SF1523RF927DWB

- KOM 100 SF 1500 IP23 9VWW RF FL DA WH/BK

Description:

Finish: Matte Traffic white RAL 9016

Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.325 lm °K: 2700 Plum: 13,9W CRI: 90 Efficacy: 95,3 lm/w R9: 58 UGR: <19 3 MacAdam:

 Type:
 COB
 Power Supply:
 220-240V 50/60Hz

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Gear:
 Adjustable DALI

Power: 13W

Light output tolerance +/- 10%

EPD

Tel. +34937366800 Web www.lamp.es

KOMBIC 100 SURFACE



K11SF1523RF927DWB


KOM 100 SF 1500 IP23 9VWW RF FL DA WH/BK


PHOTOMETRIC DATA:


K11SF1523RF927DWB $_{\eta}$ = 100% Imax = 2200 cd/klm UTE:


CIE: 98 99 100 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH