KOMBIC 100 SURFACE

K11SF1523RW927DBW

- KOM 100 SF 1500 IP23 9VWW RF WFL DA B/W

Description:

Finish: Matte Traffic white RAL 9016 Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

| Light output: | 1.168 lm | °K : | 2700 |
|---------------|--------------------------|---------------|------------------|
| Plum: | 13,9W | CRI : | 90 |
| Efficacy: | 84 lm/w | R9 : | 58 |
| UGR: | <19 | MacAdam: | 3 |
| Туре: | СОВ | Power Supply: | 220-240V 50/60Hz |
| LED Lifetime: | 50.000 L80 B10 (Ta=25⁰C) | Gear: | Adjustable DALI |
| Power: | 13W | | |

Light output tolerance +/- 10%

EPD




KOMBIC 100 SURFACE


K11SF1523RW927DBW

KOM 100 SF 1500 IP23 9VWW RF WFL DA B/W



PHOTOMETRIC DATA :





LAMP reserves the right to change the technical specifications of their products. These changes will allow the continual improvement of the products and will also ensure the conformity to current legal changes. Updated information is always available in our website www.lamp.es

Product datasheet

KOMBIC 100 SURFACE

ACCESORIES :

Suspension



Product code: K11SUADLATBK

Description: KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH

Description: KOMBIC 100 SF ADAPT. LATERAL CABLE WH

Worktitude for light