KOMBIC 100 SURFACE



K11SF1523RW927DMW

- KOM 100 SF 1500 IP23 9VWW RF WFL DA M/W

Description:

Finish: Matte Traffic white RAL 9016

Weight: 712 g

Installation: Recessed

TECHNICAL SPECIFICATIONS:

Light output: 1.264 lm °K: 2700 Plum: 13,9W CRI: 90 Efficacy: 90,9 lm/w R9: 58 Type: СОВ 3 MacAdam:

 LED Lifetime:
 50.000 L80 B10 (Ta=25°C)
 Power Supply:
 220-240V 50/60Hz

 Power:
 13W
 Gear:
 Adjustable DALI

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF1523RW927DMW

KOM 100 SF 1500 IP23 9VWW RF WFL DA M/W


PHOTOMETRIC DATA:


K11SF1523RW927DMW η = 100%


lmax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH