KOMBIC 100 SURFACE



K11SF1523RW927NWW

- KOMBIC 100 SF 1500 IP23 9VWW RF WFL W/W



Description:

Finish: Matte white RAL 9010

Weight: 502 g

Installation: Surface

TECHNICAL SPECIFICATIONS:

Light output: 1.264 lm °K: 2700 Plum: 14,1W CRI: 90 Efficacy: 89,6 lm/w R9: 58 Type: СОВ MacAdam: 3

LED Lifetime: 50.000 L80 B10 (Ta=25°C) **Power Supply:** 220-240V 50/60Hz

Power: 13W Gear: Electronic

Light output tolerance +/- 10%

EPD

KOMBIC 100 SURFACE



K11SF1523RW927NWW

KOMBIC 100 SF 1500 IP23 9VWW RF WFL W/W


PHOTOMETRIC DATA:


K11SF1523RW927NWW η = 100%


lmax = 1215 cd/klm


UTE: 1,00A


CIE: 94 97 99 100 100




















KOMBIC 100 SURFACE



ACCESORIES:

Suspension



Product code: K11SUADLATBK

Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE BK



Product code: K11SUADLATWH Description:

KOMBIC 100 SF ADAPT. LATERAL CABLE WH